

**piek mini** Design: Sebastian David Büscher

für unbefestigte Beet- und Grünflächen for unpaved beds and greens

Lichttechnik:  
230V LED  
2700K  
L70/50.000 h

dimmbar

Zuleitung:  
1 m Leuchte (05RN8-F 2x0,75 mm<sup>2</sup>) + 2 m Driver (05RN8-F 3G1,0 mm<sup>2</sup>) inkl. Schutzkontaktstecker anschlussfertig

ortsveränderlich

Material:  
Kopf: Aluminiumguss pulverbeschichtet + Klarglas  
Stab: Edelstahl pulverbeschichtet

Schutzart:  
Leuchte: IP65 . Driver: IP67 . Stecker: IP44

Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse E

Lichtrichtung:



light technology:  
230V LED  
2700K  
L70/50.000 h

dimmable

supply cable:  
1 m luminaire (05RN8-F 2x0,75 mm<sup>2</sup>) + 2 m driver (05RN8-F 3G1,0 mm<sup>2</sup>) incl. safety plug ready to connect


movable

material:  
head: aluminium die-casting powder-coated + clear glass; pole: stainless steel powder-coated

protection class:  
luminaire: IP65 . driver: IP67 . plug: IP44

This product contains a light source of energy efficiency class E

light direction:



Farbe  
colour

Art.-Nr.  
item no.

Systemleistung  
system performance



anthracite  
RAL 7016

93077-AN

4 W/192 lm



cool brown

93077-CB

4 W/192 lm



deep black  
RAL 9005

93077-BL

4 W/192 lm

+ Optional mit CH-Stecker . with CH-plug as an option

Größe in mm  
size in mm