

# Classic Ifökupa


The Classic series is an old favourite of our assortment. Ideal in most areas where functionality and timeless design are the key words. Classic is available in different combinations with a matt opal, shiny opal or a clear glass shade.

EAN / GTIN	7312904082505
E-number	7502768
Article no.	4082-500-10
Type designation	52726

## Specification

Base colourWhite (NCS S 1502-G50Y)GlassShiny opal glassGlass thread (mm)84,5 mmGlass gasketSiliconeWeight1,15 kgDiameter (mm)170Length/Depth (mm)165Lamp holderE27Light sourceE27, max 75W (not included)EffectMax 75WRated voltage230VIP classIP54Insulation classIID classNoIK classIK02Ta-30 - +25InstallationWallCC measurement (mm)60-66Knock out opening1 - demands glandsCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionMantle screwFamilyClassicDesignIfö Electric	Material	Porcelain
GlassBathy spaceGlass gasketSiliconeWeight1,15 kgDiameter (mm)170Length/Depth (mm)165Lamp holderE27Light sourceE27, max 75W (not included)EffectMax 75WRated voltage230VIP classIP54Insulation classIID classNoIK classIK02Ta-30 - +25InstallationWallCC measurement (mm)60-66Knock out opening1 - demands glandsCable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesConnectionMantle screwFamilyClassic	Base colour	White (NCS S 1502-G50Y)
Glass gasketSiliconeWeight1,15 kgDiameter (mm)170Length/Depth (mm)165Lamp holderE27Light sourceE27, max 75W (not included)EffectMax 75WRated voltage230VIP classIP54Insulation classIID classNoIK classIK02Ta-30 - +25InstallationWallCC measurement (mm)60-66Knock out opening1 - demands glandsCable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionMantle screwFamilyClassic	Glass	Shiny opal glass
Weight1,15 kgDiameter (mm)170Length/Depth (mm)165Lamp holderE27Light sourceE27, max 75W (not included)EffectMax 75WRated voltage230VIP classIP54Insulation classIID classNoIK classIK02Ta-30 - +25InstallationWallCC measurement (mm)60-66Knock out opening1 - demands glandsCable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionMantle screwFamilyClassic	Glass thread (mm)	84,5 mm
Diameter (mm)170Length/Depth (mm)165Lamp holderE27Light sourceE27, max 75W (not included)EffectMax 75WRated voltage230VIP classIP54Insulation classIID classNoIK classIK02Ta-30 - +25InstallationWallCC measurement (mm)60-66Knock out opening1 - demands glandsCable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionMantle screwFamilyClassic	Glass gasket	Silicone
Length/Depth (mm)165Lamp holderE27Light sourceE27, max 75W (not included)EffectMax 75WRated voltage230VIP classIP54Insulation classIID classNoIK classIK02Ta-30 - +25InstallationWallCC measurement (mm)60-66Knock out opening1 - demands glandsCable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionMantle screwFamilyClassic	Weight	1,15 kg
Lamp holderE27Light sourceE27, max 75W (not included)EffectMax 75WRated voltage230VIP classIP54Insulation classIID classNoIK classIK02Ta-30 - +25InstallationWallCC measurement (mm)60-66Knock out opening1 - demands glandsCable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionMantle screwFamilyClassic	Diameter (mm)	170
Light sourceE27, max 75W (not included)EffectMax 75WRated voltage230VIP classIP54Insulation classIID classNoIK classIK02Ta-30 - +25InstallationWallCC measurement (mm)60-66Knock out opening1 - demands glandsCable glandsBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionMantle screwFamilyClassic	Length/Depth (mm)	165
EffectMax 75WRated voltage230VIP classIP54Insulation classIID classNoIK classIK02Ta-30 - +25InstallationWallCC measurement (mm)60-66Knock out opening1 - demands glandsCable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionMantle screwFamilyClassic	Lamp holder	E27
Rated voltage230VRated voltage230VIP classIP54Insulation classIID classNoIK classIK02Ta-30 - +25InstallationWallCC measurement (mm)60-66Knock out opening1 - demands glandsCable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionMantle screwFamilyClassic	Light source	E27, max 75W (not included)
IP classIP54Insulation classIID classNoIK classIK02Ta-30 - +25InstallationWallCC measurement (mm)60-66Knock out opening1 - demands glandsCable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionMantle screwFamilyClassic	Effect	Max 75W
Insulation classIID classNoIK classIK02Ta-30 - +25InstallationWallCC measurement (mm)60-66Knock out opening1 - demands glandsCable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionMantle screwFamilyClassic	Rated voltage	230V
D classNoIK classIK02Ta-30 - +25InstallationWallCC measurement (mm)60-66Knock out opening1 - demands glandsCable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionMantle screwFamilyClassic	IP class	IP54
IK classIK02Ta-30 - +25InstallationWallCC measurement (mm)60-66Knock out opening1 - demands glandsCable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionMantle screwFamilyClassic	Insulation class	II
Ta-30 - +25InstallationWallCC measurement (mm)60-66Knock out opening1 - demands glandsCable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionMantle screwFamilyClassic	D class	No
InstallationWallCC measurement (mm)60-66Knock out opening1 - demands glandsCable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionMantle screwFamilyClassic	IK class	IK02
CC measurement (mm)60-66Knock out opening1 - demands glandsCable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionMantle screwFamilyClassic	Та	-30 - +25
Knock out opening1 - demands glandsCable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionMantle screwFamilyClassic	Installation	Wall
Cable inletBottom inletCable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionMantle screwFamilyClassic	CC measurement (mm)	60-66
Cable glandsBottom inletCable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionMantle screwFamilyClassic	Knock out opening	1 - demands glands
Cable area, maxMax 2 x 2,5 mm2BridgingYesSurface mounted cableYesConnectionMantle screwFamilyClassic	Cable inlet	Bottom inlet
BridgingYesSurface mounted cableYesConnectionMantle screwFamilyClassic	Cable glands	Bottom inlet
Surface mounted cable Yes   Connection Mantle screw   Family Classic	Cable area, max	Max 2 x 2,5 mm2
Connection Mantle screw   Family Classic	Bridging	Yes
Family Classic	Surface mounted cable	Yes
	Connection	Mantle screw
Design Ifö Electric	Family	Classic
	Design	Ifö Electric





#### Luminaire specific information

Angeled 14 degrees.

### Maintenance

Disconnect the power to the luminaire. Unscrew the glass and clean it. Do not use detergents that contain solvents. Replace light source if necessary. Check the gasket and replace it if necessary. Screw the shade back on.

## Spare parts

Iföglobe shiny opal, Article no.: 1-6112 Gasket silkon for thread 84,5 mm, Article no.: 02786-9

If the luminaire is modified the person responsible for the modification shall be considered manufacturer. Subject to errors in text. We reserve the right to change the technical specifications (without notice).