









Description

- BENDZ compact wall light fitting for ambient Housing: Co-extruded polycarbonate/PMMA lighting
- Color: COAL (RAL 7021)
- External polished 316L stainless steel unit cover painted COAL (RAL 7021)
- · Clear diffuser
- End caps & fixing straps: Stainless steel 316L painted COAL (RAL 7021)
- for inside/outside use
- External metal parts in 316L stainless steel and screws in A4 stainless steel
- · E27 socket fixed on the dismountable end cap
- Moulded EPDM gaskets



Light specifications and controlling

- With 1 matt LED E27 filament lamp (4W 2700K)
- Net luminous flux: 280 lm



Installation and maintenance

- Length illuminating surface: 133 mm
- Total length: 270 mm
- Provided with 0,50m 3G1,5 cable with tinned copper meshwork under transparent tubing
- Connection to 3x2.5mm² automatic terminal block
- 2 reinforced fixing straps in stainless steel with HSHC screw in A2 stainless steel with variable centre distance and allowing 360° orientation
- Provided with stainless steel cable plate 316L, for indoor use (IP 40), for earthing
- · Installation in vertical position, cable gland positioned downwards
- · Maintenance by removal of the end cap











Characteristics

· Warranty: 5 years

• Operating temperature: -20°C to +30°C

• Protection: IP66/IP68/IP69K

• Resistance to IK shocks: IK10

Class I

• Power consumption: 4 W

• T°C with incandescent wires: 650°C

• Weight: 0,8 kg

· Designed and made in France