

Classic Globe 150 LED 3000K


The Classic series is an old favourite of our assortment. Ideal in most areas where functionality and timeless design are the key words. Classic is available in different combinations and are also available with a grey or a brown glazed base as option.

EAN / GTIN	7312906044822
E-number	7502734
Article no.	6044-800-10
Type designation	52726/LED

Specification

GlassMatt opcGlass thread (mm)84,5 mmGlass thread (mm)84,5 mmGlass gasketSiliconeWeight0,98 kgDiameter (mm)150Height (mm)193Lamp holderLEDLight sourceLED modeEffect8WLumen, light source800lmLumen, luminarire687Colour temperature3000KMacAdam3Life spanL80/B10RaMin 90Rated voltage230VDimmableRC modeIP classIP54Insulation classIEnergy classF	-
Glass thread (mm)84,5 mmGlass gasketSiliconeWeight0,98 kgDiameter (mm)150Height (mm)193Lamp holderLEDLight sourceLED modeEffect8WLumen, light source800lmLumen, luminarire687Colour temperature3000KMacAdam3Life spanL80/B10RaMin 90Rated voltage230VDimmableRC modeIP classIP54Insulation classIEnergy classF	
Glass gasketSiliconeWeight0,98 kgDiameter (mm)150Height (mm)193Lamp holderLEDLight sourceLED modeEffect8WLumen, light source800lmLumen, luminarire687Colour temperature3000KMacAdam3Life spanL80/B10RaMin 90Rated voltage230VDimmableRC modeIP classIP54Insulation classIEnergy classF	
Weight0,98 kgDiameter (mm)150Height (mm)193Lamp holderLEDLight sourceLED modeEffect8WLumen, light source800lmLumen, luminarire687Colour temperature3000KMacAdam3Life spanL80/B10RaMin 90Rated voltage230VDimmableRC modeIP classIP54Insulation classIEnergy classF	lule, 8W **
Diameter (mm)150Height (mm)193Lamp holderLEDLight sourceLED modeEffect8WLumen, light source800lmLumen, luminarire687Colour temperature3000KMacAdam3Life spanL80/B10RaMin 90Rated voltage230VDimmableRC modeIP classIP54Insulation classIEnergy classF	lule, 8W **
Height (mm)193Lamp holderLEDLight sourceLED modEffect8WLumen, light source800lmLumen, luminarire687Colour temperature3000KMacAdam3Life spanL80/B10RaMin 90Rated voltage230VDimmableRC modeIP classIP54Insulation classIEnergy classF	lule, 8W **
Lamp holderLEDLight sourceLED modEffect8WLumen, light source800lmLumen, luminarire687Colour temperature3000KMacAdam3Life spanL80/B10RaMin 90Rated voltage230VDimmableRC modeIP classIP54Insulation classIEnergy classF	lule, 8W **
Light sourceLED modEffect8WLumen, light source800lmLumen, luminarire687Colour temperature3000KMacAdam3Life spanL80/B10RaMin 90Rated voltage230VDimmableRC modeIP classIP54Insulation classIEnergy classF	lule, 8W **
Effect8WLumen, light source800lmLumen, luminarire687Colour temperature3000KMacAdam3Life spanL80/B10RaMin 90Rated voltage230VDimmableRC modeIP classIP54Insulation classIEnergy classF	lule, 8W **
Lumen, light source800lmLumen, luminarire687Colour temperature3000KMacAdam3Life spanL80/B10RaMin 90Rated voltage230VDimmableRC modeIP classIP54Insulation classIEnergy classF	
Lumen, luminarire687Colour temperature3000KMacAdam3Life spanL80/B10RaMin 90Rated voltage230VDimmableRC modeIP classIP54Insulation classIEnergy classF	
Colour temperature3000KMacAdam3Life spanL80/B10RaMin 90Rated voltage230VDimmableRC modeIP classIP54Insulation classIEnergy classF	
MacAdam3Life spanL80/B10RaMin 90Rated voltage230VDimmableRC modeIP classIP54Insulation classIEnergy classF	
Life span L80/B10 Ra Min 90 Rated voltage 230V Dimmable RC mode IP class IP54 Insulation class I Energy class F	
RaMin 90Rated voltage230VDimmableRC modeIP classIP54Insulation classIEnergy classF	
Rated voltage230VDimmableRC modeIP classIP54Insulation classIEnergy classF	: 47 000 h
DimmableRC modeIP classIP54Insulation classIEnergy classF	
IP class IP54 Insulation class I Energy class F	
Insulation class I Energy class F)
Energy class F	
D class No	
IK class IK02	
Ta -30 - +2	5
Installation Wall	
CC measurement (mm) 60-66	
Knock out opening 1 - demo	ands glands
Cable inlet Bottom i	nlet
Cable glands Bottom i	nlet
Cable area, max Max 3 x	2,5 mm2
Bridging Yes	
Surface mounted cable Yes	
Connection Termina	
Family Classic C	block
Design Ifö Electr	





Luminaire specific information

Angeled 14 degrees.

Maintenance

Disconnect the power to the luminaire. Unscrew the glass and clean it. Do not use detergents that contain solvents. Replace light source if necessary. Check the gasket and replace it if necessary. Screw the shade back on.

Spare parts

Shade globe, Ø 150 mm matt opal, Article no.: 1-6108-1 Gasket silkon for thread 84,5 mm, Article no.: 02786-9 LED module 8W - 3000K, Article no.: 1-54057-930

** The device must under no circumstances be connected to the same phase as a magnetic ballast or other older fluorescent luminaires as these luminaires can generate overvoltage transients outside of EU regulatory standards when switched off or on. The luminaire can permanently damage or completely cease to function when connected.

If the luminaire is modified the person responsible for the modification shall be considered manufacturer. Subject to errors in text. We reserve the right to change the technical specifications (without notice).